


S5N**DATALOGIC**

(*) Stainless steel models. ATEX II 3DG

EXTENDED RANGE OF STANDARD “ONE FOR ALL” PHOTOELECTRIC TUBULAR M18 SENSORS

- All optic functions
- Improved EMI immunity
- Improved ambient light immunity
- Improved laser safety level
- M18 flat plastic with universal mounting
- Short plastic housing models
- Available in M18 metal housing
- Stainless steel housing models
- Axial or radial optics, cable or connector
- Standard 4-wire NO-NC NPN or PNP output
- M12 pigtail models available
- IO-Link connectivity V1.1 with double channel

APPLICATIONS

- Processing and Packaging machinery
- Conveyor lines, material handling
- Ceramics intralogistics
- Automated warehousing

S5N		
Through beam		0...25 m (S5N-PP/NN; S5N-Px/Mx...PK/NK models) 0...20 m (S5N-SA/NA models) 0...60 m (class 1 LASER S5N...PP/NN models)
Retroreflective (on R2 reflector)		0,1...4 m (S5N-PP/NN; S5N-Px/Mx...PK/NK models)
Polarized retroreflective (on R2 reflector)		0,1...3m (S5N-Px/Mx...PK/NK models) 0,1...4 m (S5N...PP/NN; S5N-SA/NA models) 0,1...16 m (class 1 LASER S5N...PP/NN models)
Retroreflective for transparent (on R2 reflector)		0,1...0,8 m (S5N-SA/NA) 0,1...1,3 m (S5N...PP/NN models)
Diffuse proximity		short distance 0...100 mm (all models) medium distance 0...400 mm (S5N...PP/NN models) medium distance 0...350 (S5N-SA/NA models) medium distance 0...450 (S5N-Px/Mx...PK/NK models) long distance 0...700 ammm (S5N...PP/NN models) long distance Laser 0...350 mm (S5N...PP/NN models)
Fixed focus		50 mm (S5N-SA/NA models) 100 mm (S5N...PP/NN models)
Background suppression		40...120 mm (S5N-SA/NA models) 50...150 mm (S5N...PP/NN models)
Through beam with fiber optic		0...100 mm (S5N...PP/NN models)
Diffuse proximity with fiber optic		0...30 mm (S5N...PP/NN models)
Contrast sensor		10 ±2 mm (S5N...PP/NN models)
Luminescence sensor		0...20 mm (S5N...PP/NN models)
Power supply	Vdc	10...30 V
	Vac	
	Vac/dc	
Output	PNP	•
	NPN	•
	NPN/PNP	
	relay	
	other	IO-Link v 1.1
Connection	cable	•
	connector	•
	pig-tail	•
Approximate dimensions (mm)		M18 x (see mechanical drawings)
Housing material		PBT, Nickel plated Brass (S5N-PP/NN; S5N-Px/Mx...PK/NK models) ABS, AISI 316 L Stainless steel inox (S5N-SA/NA models)
Mechanical protection		IP67 (S5N-PP/NN; S5N-Px/Mx...PK/NK models) IP65 - IP67 - IP69K (S5N-SA/NA)

TECHNICAL DATA


Power supply	10 ... 30 Vdc (limit values all models)
Ripple	2 Vpp max. (all models)
Consumption (output current excluded)	35 mA max. (all models)
Light emission	red LED 630 nm (mod. S5N...D00/E01, S5N-PA/MA...M03) red LED 660 nm (mod. S5N...B01...PP/NN/PK/NK; S5N...T01...PP/NN) - (mod. S5N-SA/NA...B/D/T/M) red LED 670 nm (mod. S5N-PS/MS...M03...PP/NN) IR LED 880 nm - (mod. S5N-Px/Mx...A00/C01/C10/C21/G00...PP/NN/PK/NK) - (mod. S5N-SA/NA...A/C/G) white LED 400-700 nm (mod. S5N...W03...PP/NN) UV LED 370 nm (mod. S5N...U03...PP/NN) red Laser 650 nm (mod. S5N-PH/PL...G00/B01/C01...PP/NN)
Setting	sensitivity trimmer 270° and without trimmer model (see mech drawings) 4 turns sensitivity trimmer (mod. S5N-Px/Mx...M01...PK/NK) teach-in push-button (mod. S5N...M03/W03/U03...PP/NN)
Operating mode	LIGHT mode on N.O. output / DARK mode on N.C. output (mod.S5N...C01/C10/C21/D00/M03/U03...PP/NN) DARK mode on N.O. output / LIGHT mode on N.C. output (mod.S5N...A00/B01/E01/F01/T01/W03...PP/NN) L/D input white wire or pin 2, if pin not connected on S5N-Px/Mx...PK/NK: LIGHT mode (mod. S5N-Px/Mx...C/D/M...PK/NK) DARK mode (mod. S5N-Px/Mx...A/B/T/F...PK/NK) white wire or pin 2 connected to: 0 V DARK mode, +Vcc LIGHT mode
Indicators	yellow OUTPUT LED (S5N, excl. mod. G00) green STABILITY LED (mod. S5N...B01/C01/C21/E01/F01/W03/U03), POWER LED (mod. S5N...G00) green/red READY/ERROR LED (mod. S5N...M03...PP/NN)
Output	PNP or NPN; NO; NC (mod. S5N...PP/NN) PNP or NPN (mod. S5N-Px/Mx...PK/NK) IO-Link v 1.1 (mod.S5N...OZ)
IO-Link interface	(mod.S5N...OZ) v 1.1, com 2, 38,4 kBaud, 32 bit process data, 5 ms cycle time LED emission model, 8 ms cycle time LASER emission model
Output current	100 mA max. (all models)
Saturation voltage	2 V max. (all models)
Response time	0,5 ms (mod. S5N...A00/B01/T01/C10/C21/C01/D00/E01/U03...PP/NN) - (mod. S5N-Px/Mx...D00...PK/NK) 2 ms (mod. S5N...F01/G00...PP/NN) - (mod. S5N-Px/Mx...F00...PK/NK) 1 ms (mod. S5N...M03...PP/NN) - (mod. S5N-Px/Mx...A/B/C/T/M...PK/NK) 100 µs (mod. S5N...W03...PP/NN) 333 µs (mod. S5N-PH/PL...PP/NN Laser emission models)
Switching frequency	1 kHz (mod. S5N...A00/B01/T01/C10/C21/C01/D00/E01/U03...PP/NN) - (mod. S5N-Px/Mx...D00...PK/NK) 250 Hz (mod. S5N...F01/G00...PP/NN) - (mod. S5N-Px/Mx...F00...PK/NK) 500 Hz (mod. S5N...M03...PP/NN) - (mod. S5N-Px/Mx...A/B/C/T/M...PK/NK) 100 µs (mod. S5N...W03...PP/NN) 333 µs (mod. S5N...PP/NN Laser emission models)
Connection	M12 4-pole connector, 2 m cable Ø 4 mm, 150 mm length Ø 4 mm cable with M12 4-pole connector
Dielectric strength	500 Vac, 1 min between electronics and housing
Insulating resistance	>20 MΩ, 500 Vdc between electronics and housing
Electrical protection	class 2
Mechanical protection	IP67 (S5N-PP/NN; S5N-Px/Mx...PK/NK models) IP65 - IP67 - IP69K (S5N-SA/NA)
Ambient light rejection	according to EN 60947-5-2
Vibrations	0,5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
Shock resistance	11 ms (30 G) 6 shock for every axis (EN60068-2-27)
Housing material	PBT, Nickel plated Brass (S5N-Px/Mx...PP/NN/PK/NK models) ABS, AISI 316 L Stainless steel inox (S5N-SA/NA models)
Lens material	PMMA (all models)
Operating temperature	-25 ... 55 °C (Laser mod.) -10 ... 50 °C
Storage temperature	-25 ... 70 °C
Weight	Plastic version 75 g max. cable vers. (90 g max. mod. M03), 25 g max. conn. vers. (40 g max. mod. M03) Metal version 110 g max. cable vers. (125 g max. mod. M03), 60 g max. conn. vers. (75 g max. mod. M03)

DIMENSIONS


S5N...NN/PP MODELS

PLASTIC


AXIAL VERSION



RADIAL VERSION




FIBRE OPTIC VERSION




METAL


AXIAL VERSION





RADIAL VERSION





FIBRE OPTIC VERSION





PLASTIC



PLASTIC




PLASTIC




S5N-SA MODELS

PLASTIC


M12 connector version




Cable version




Through beam emitter - M12 connector version




Background suppression - M12 connector version



Through beam emitter - cable version



Diffuse proximity - cable version




DIMENSIONS


S5N-NA MODELS

STAINLESS STEEL


M12 connector version




Through beam emitter - M12 connector version



Background suppression - M12 connector version



Pig-tail version





CONNECTIONS



S5N...PP/NN MODELS

CABLE

Through beam emitter




M12 CONNECTOR




S5N-Px/Mx...PK/NK MODELS

G00 MODEL





A00/B01/C01/C10/C20/F00 MODELS



S5N...NA/SA MODELS

Cable and Pig-tail

M12 connector



INDICATORS AND SETTINGS

S5N...PP/NN MODELS


S5N-XX...A00/B01/C01/C21/E01/F01/T01



- A** OUTPUT status LED Yellow
STABILITY LED Green (Only Receiver)
POWER ON LED Green (Only Emitter)
- B** Adjustment trimmer (receiver)


Single-turn trimmer for sensitivity adjustment. Rotate in a clockwise direction to increase the operating distance.

S5N-XX-U03



- A** OUTPUT status LED Yellow
READY LED Green
LED Red error
- B** Teach-in push-button

S5N-XX-M03/W03




- A** OUTPUT status LED Yellow
READY LED Green
- B** Teach-in push-button

Teach-in button for setting.


EASYtouch™ provides two setting modes: standard or fine, both obtained by pressing the push-button only once. Please refer to instructions manual for operating details.

S5N-XX-A00/C10/D00



- A00/C10**
A OUTPUT status LED Yellow
- G00**
OUTPUT status LED yellow (Only Emitter G00)

S5N-Px/Mx...PK/NK MODELS




- A** OUTPUT status LED;
POWER ON LED on G00 model
- B** Adjustment trimmer (B01, C01 models)
- C** M12 connector
- D** Cable connection


Trimmer for sensitivity adjustment. Rotate in a clockwise direction to increase the operating distance.

S5N...SA/NA MODELS


Plastic/metal case with trimmer, M12 connector




A01, B01, C11, C31, T01, F01, M01




G01



Plastic, no trimmer, Cable, Pig Tail



A00, B00, C10, C00, T01, D50




G00

F00



DETECTION DIAGRAMS

S5N...PP/NN MODELS


THROUGH BEAM (G/F) INFRARED EMISSION







Recommended operating distance
Maximum operating distance




THROUGH BEAM (G/F) LASER RED EMISSION





Operating distance



RETROREFLECTIVE (A) INFRARED EMISSION



■ Operating distance







RETROREFLECTIVE POLARIZED (B) RED EMISSION




■ Recommended operating distance
■ Maximum operating distance

High efficiency reflectors can be used to obtain larger operating distances. Refer to **Reflectors** (A.01).







RETROREFLECTIVE POLARIZED (B) LASER RED EMISSION




■ Operating distance

High efficiency reflectors can be used to obtain larger operating distances. Refer to **Reflectors** (A.01).





RETROREFLECTIVE TRANSPARENT (T) RED EMISSION




■ Recommended operating distance
■ Maximum operating distance





High efficiency reflectors can be used to obtain larger operating distances. Refer to **Reflectors**.



ENERGETIC DIFFUSED (C) SHORT INFRARED EMISSION





Recommended operating distance
Maximum operating distance




ENERGETIC DIFFUSED (C) MID INFRARED EMISSION







Recommended operating distance
Maximum operating distance




ENERGETIC DIFFUSED (C) LONG INFRARED EMISSION




Recommended operating distance
Maximum operating distance




FIXED FOCUS (D) RED EMISSION




Operating distance




Excess gain - axial



Detection area - axial




Excess gain - radial




Detection area - radial


DIFFUSED (C) LASER RED EMISSION




Operating distance




Detection area - axial



Resolution - axial




Detection area - radial




Resolution - radial


BACKGROUND SUPPRESSOR (M) AXIAL RED EMISSION



Operating distance




Detection difference with EASYtouch™ acquisition




Detection difference with EASYtouch™ fine acquisition


BACKGROUND SUPPRESSOR (M) RADIAL RED EMISSION



Operating distance




Detection difference with EASYtouch™ acquisition



Detection difference with fine acquisition





FIBER OPTIC (E) RED EMISSION



Operating distance with standard fibers


Standard Fiber-optics:
OF-42-ST-20 proximity
OF-43-ST-20 through beam

High efficiency fiber-optics or accessory lenses
can be used to obtain larger operating distances.




* standard Fiber-optics

MARK READER (W) WHITE EMISSION




Operating distance




Operating distance

LUMINESCENCE (U) UV EMISSION











Operating distance



Operating distance

S5N...PK/NK MODELS












Note: the diagrams indicate the detection area typical of the axial optic versions; the maximum operating distance of the radial optic versions decreases as indicated in the tables given below

Recommended operating distance
Maximum operating distance

S5N-SA/NA MODELS



MODEL SELECTION AND ORDER INFORMATION

S5N - STANDARD PLASTIC HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-PA...PP/NN/OZ)						
OPTIC FUNCTION	EMISSION	CONNECTION	OUTPUT	MODEL	ORDER NO.	
Retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-A00-NN	952002091	
		M12 Connector	PNP	S5N-PA-2-A00-PP	952002081	
			NPN	S5N-PA-5-A00-NN	952002111	
			PNP	S5N-PA-5-A00-PP	952002101	
2m Cable		NPN	S5N-PA-2-B01-NN	952001611		
M12 Connector		PNP	S5N-PA-2-B01-PP	952001011		
		NPN	S5N-PA-5-B01-NN	952001501		
		PNP	S5N-PA-5-B01-PP	952001021		
Polarized retroreflective	LED, Radial optic	2m Cable	IO-Link	S5N-PA-5-B01-OZ	952002200	
			NPN	S5N-PR-2-B01-NN	952001781	
		PNP	S5N-PR-2-B01-PP	952001031		
		M12 Connector	NPN	S5N-PR-5-B01-NN	952001721	
	PNP		S5N-PR-5-B01-PP	952001041		
	LASER, Axial optic	2m Cable	NPN	S5N-PL-2-B01-NN	952001871	
		M12 Connector	PNP	S5N-PL-2-B01-PP	952001361	
			NPN	S5N-PL-5-B01-NN	952001841	
			PNP	S5N-PL-5-B01-PP	952001371	
	LASER, Radial optic	2m Cable	IO-Link	S5N-PL-5-B01-OZ	952002250	
			NPN	S5N-PH-2-B01-NN	952001951	
		PNP	S5N-PH-2-B01-PP	952001941		
		M12 Connector	NPN	S5N-PH-5-B01-NN	952001971	
	PNP		S5N-PH-5-B01-PP	952001961		
	Long Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C01-NN	952001621
			M12 Connector	PNP	S5N-PA-2-C01-PP	952001051
NPN				S5N-PA-5-C01-NN	952001511	
PNP				S5N-PA-5-C01-PP	952001061	
LED, Radial optic		2m Cable	IO-Link	S5N-PA-5-C01-OZ	952002210	
			NPN	S5N-PR-2-C01-NN	952001791	
		M12 Connector	PNP	S5N-PR-2-C01-PP	952001071	
			NPN	S5N-PR-5-C01-NN	952001731	
LASER, Axial optic		M12 Connector	PNP	S5N-PR-5-C01-PP	952001081	
			2m Cable	NPN	S5N-PL-2-C01-NN	952001881
			PNP	S5N-PL-2-C01-PP	952001381	
		LASER, Radial optic	M12 Connector	NPN	S5N-PL-5-C01-NN	952001851
PNP				S5N-PL-5-C01-PP	952001391	
IO-Link				S5N-PL-5-C01-OZ	952002260	
M12 Connector			NPN	S5N-PH-2-C01-NN	952001991	
		PNP	S5N-PH-2-C01-PP	952001981		
	NPN	S5N-PH-5-C01-NN	952002011			
	PNP	S5N-PH-5-C01-PP	952002001			
Short Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C10-NN	952001631	
		M12 Connector	PNP	S5N-PA-2-C10-PP	952001241	
			NPN	S5N-PA-5-C10-NN	952001521	
			PNP	S5N-PA-5-C10-PP	952001251	
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-C10-NN	952001801	
		M12 Connector	PNP	S5N-PR-2-C10-PP	952001491	
			NPN	S5N-PR-5-C10-NN	952001741	
			PNP	S5N-PR-5-C10-PP	952001481	
Medium Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C21-NN	952002171	
		M12 Connector	PNP	S5N-PA-2-C21-PP	952002161	
			NPN	S5N-PA-5-C21-NN	952002191	
			PNP	S5N-PA-5-C21-PP	952002181	
	Fixed focus	LED, Axial optic	2m Cable	NPN	S5N-PA-2-D00-NN	952001641
			M12 Connector	PNP	S5N-PA-2-D00-PP	952001091
				NPN	S5N-PA-5-D00-NN	952001531
				PNP	S5N-PA-5-D00-PP	952001101
Through beam receiver	LED, Radial optic	2m Cable	NPN	S5N-PR-2-D00-NN	952001811	
		M12 Connector	PNP	S5N-PR-2-D00-PP	952001111	
			NPN	S5N-PR-5-D00-NN	952001751	
			PNP	S5N-PR-5-D00-PP	952001121	
Fiber optic	LED, Axial optic	2m Cable	NPN	S5N-PA-2-E01-NN	952001651	
		M12 Connector	PNP	S5N-PA-2-E01-PP	952001131	
			NPN	S5N-PA-5-E01-NN	952001541	
			PNP	S5N-PA-5-E01-PP	952001141	
Through beam receiver	LED, Axial optic	2m Cable	NPN	S5N-PA-2-F01-NN	952001661	
		M12 Connector	PNP	S5N-PA-2-F01-PP	952001151	
			NPN	S5N-PA-5-F01-NN	952001551	
			PNP	S5N-PA-5-F01-PP	952001161	
Through beam receiver	LED, Radial optic	2m Cable	NPN	S5N-PR-2-F01-NN	952001821	
		M12 Connector	PNP	S5N-PR-2-F01-PP	952001171	
			NPN	S5N-PR-5-F01-NN	952001761	
			PNP	S5N-PR-5-F01-PP	952001181	
	LASER, Axial optic	2m Cable	NPN	S5N-PL-2-F01-NN	952001891	
		M12 Connector	PNP	S5N-PL-2-F01-PP	952001401	
			NPN	S5N-PL-5-F01-NN	952001861	
			PNP	S5N-PL-5-F01-PP	952001411	
	LASER, Radial optic	2m Cable	NPN	S5N-PH-2-F01-NN	952002031	
		M12 Connector	PNP	S5N-PH-2-F01-PP	952002021	
			NPN	S5N-PH-5-F01-NN	952002051	
			PNP	S5N-PH-5-F01-PP	952002041	
Through beam emitter	LED, Axial optic	2m Cable	-	S5N-PA-2-G00-XG	952001191	
		M12 Connector	-	S5N-PA-5-G00-XG	952001201	
	LED, Radial optic	2m Cable	-	S5N-PR-2-G00-XG	952001211	
		M12 Connector	-	S5N-PR-5-G00-XG	952001221	
	LASER, Axial optic	2m Cable	-	S5N-PL-2-G00-XG	952001421	
		M12 Connector	-	S5N-PL-5-G00-XG	952001431	
	LASER, Radial optic	2m Cable	-	S5N-PH-2-G00-XG	952002061	
		M12 Connector	-	S5N-PH-5-G00-XG	952002071	

S5N - STANDARD PLASTIC HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-PA...PP/NN/OZ)							
Background suppression	LED, Axial optic	2m Cable	NPN	S5N-PA-2-M03-NN	952001671		
			PNP	S5N-PA-2-M03-PP	952001231		
		M12 Connector	NPN	S5N-PA-5-M03-NN	952001561		
			PNP	S5N-PA-5-M03-PP	952001001		
	LED, Radial optic	M12 Connector	 IO-Link	S5N-PA-5-M03-OZ	952002230		
			PNP	S5N-PS-5-M03-PP	952001931		
		2m Cable	NPN	S5N-PS-5-M03-NN	952001921		
			PNP	S5N-PS-2-M03-PP	952001911		
			NPN	S5N-PS-2-M03-NN	952001901		
			NPN	S5N-PA-2-T01-NN	952001691		
Retroreflective for transparent	LED, Axial optic	2m Cable	PNP	S5N-PA-2-T01-PP	952001261		
			NPN	S5N-PA-5-T01-NN	952001581		
		M12 Connector	PNP	S5N-PA-5-T01-PP	952001271		
			 IO-Link	S5N-PA-5-T01-OZ	952002220		
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-T01-NN	952001831		
			PNP	S5N-PR-2-T01-PP	952001281		
		M12 Connector	NPN	S5N-PR-5-T01-NN	952001771		
			PNP	S5N-PR-5-T01-PP	952001291		
		Luminescence	LED, Axial optic	2m Cable	NPN	S5N-PA-2-U03-NN	952001701
					PNP	S5N-PA-2-U03-PP	952001301
M12 Connector	NPN			S5N-PA-5-U03-NN	952001591		
	PNP			S5N-PA-5-U03-PP	952001311		
Contrast	2m Cable			NPN	S5N-PA-2-W03-NN	952001711	
				PNP	S5N-PA-2-W03-PP	952001321	
	M12 Connector	NPN	S5N-PA-5-W03-NN	952001601			
		PNP	S5N-PA-5-W03-PP	952001331			
		 IO-Link	S5N-PA-5-W03-OZ	952002240			
S5N - STANDARD PLASTIC HOUSING - L/D INPUT MODELS (S5N-PA...PK/NK)							
Retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-A00-NK	952701072		
			PNP	S5N-PA-2-A00-PK	952701002		
		M12 Connector	NPN	S5N-PA-5-A00-NK	952701332		
			PNP	S5N-PA-5-A00-PK	952701262		
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-A00-NK	952701202		
			PNP	S5N-PR-2-A00-PK	952701132		
Polarized retroreflective	LED, Axial optic	2m Cable	NPN	S5N-PA-2-B01-NK	952701082		
			PNP	S5N-PA-2-B01-PK	952701012		
		M12 Connector	NPN	S5N-PA-5-B01-NK	952701342		
			PNP	S5N-PA-5-B01-PK	952701272		
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-B01-NK	952701212		
			PNP	S5N-PR-2-B01-PK	952701142		
		M12 Connector	PNP	S5N-PR-5-B01-PK	952701402		
			Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C01-NK
	PNP	S5N-PA-2-C01-PK				952701022	
	M12 Connector	NPN			S5N-PA-5-C01-NK	952701352	
PNP		S5N-PA-5-C01-PK			952701282		
LED, Radial optic	2m Cable	NPN		S5N-PR-2-C01-NK	952701222		
		PNP		S5N-PR-2-C01-PK	952701152		
		M12 Connector	PNP	S5N-PR-5-C01-PK	952701412		
Short Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-PA-2-C10-NK	952701102		
			PNP	S5N-PA-2-C10-PK	952701032		
		M12 Connector	NPN	S5N-PA-5-C10-NK	952701362		
			PNP	S5N-PA-5-C10-PK	952701292		
	LED, Radial optic	2m Cable	NPN	S5N-PR-2-C10-NK	952701232		
			PNP	S5N-PR-2-C10-PK	952701162		
		M12 Connector	PNP	S5N-PR-5-C10-PK	952701422		
Through beam receiver	LED, Axial optic	2m Cable	NPN	S5N-PA-2-F00-NK	952701122		
		M12 Connector	NPN	S5N-PA-5-F00-NK	952701382		
			PNP	S5N-PA-5-F00-PK	952701312		
		LED, Radial optic		PNP	S5N-PR-5-F00-PK	952701442	
Through beam emitter	LED, Axial optic	2m Cable	-	S5N-PA-2-G00-XG	952001191		
		M12 Connector	-	S5N-PA-5-G00-XG	952001201		
	LED, Radial optic	2m Cable	-	S5N-PR-2-G00-XG	952001211		
		M12 Connector	-	S5N-PR-5-G00-XG	952001221		
	LASER, Axial optic	2m Cable	-	S5N-PL-2-G00-XG	952001421		
		M12 Connector	-	S5N-PL-5-G00-XG	952001431		
	LASER, Radial optic	2m Cable	-	S5N-PH-2-G00-XG	952002061		
		M12 Connector	-	S5N-PH-5-G00-XG	952002071		
S5N - SHORT PLASTIC HOUSING - L/D INPUT MODELS (S5N-SA...)							
Polarized retroreflective	LED, Axial optic	2m Cable	NPN	S5N-SA-2-B00-NK	952301062		
			PNP	S5N-SA-2-B00-PK	952301012		
Diffuse proximity		Pig Tail M12	PNP	S5N-SA-3-B00-PK	952301122		
			NPN	S5N-SA-2-C00-NK	952301072		
		2m Cable	PNP	S5N-SA-2-C00-PK	952301022		
			PNP	S5N-SA-3-C00-PK	952301132		
Short Diffuse proximity		Pig Tail M12	PNP	S5N-SA-3-C10-PK	952301142		
Fixed Focus			PNP	S5N-SA-3-D50-PK	952301541		
Through beam receiver			PNP	S5N-SA-3-F00-PK	952301152		
Through beam emitter			-	S5N-SA-3-G00-XG	952301212		
Background suppression		M12 Connector	NPN	S5N-SA-5-M01-NK	952301351		
			PNP	S5N-SA-5-M01-PK	952301271		
Retroreflective for transparent			PNP	S5N-SA-5-T01-PK	952301241		
	NPN		S5N-SA-5-T01-NK	952301321			

S5N - METAL HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-MA...PP/NN/OZ)

Retroreflective	LED, Axial optic	2m Cable	NPN	S5N-MA-2-A00-NN	952022091		
		M12 Connector	PNP	S5N-MA-2-A00-PP	952022081		
			NPN	S5N-MA-5-A00-NN	952022111		
			PNP	S5N-MA-5-A00-PP	952022101		
Polarized retroreflective	LED, Axial optic	2m Cable	NPN	S5N-MA-2-B01-NN	952021501		
		M12 Connector	PNP	S5N-MA-2-B01-PP	952021001		
			NPN	S5N-MA-5-B01-NN	952021661		
			PNP	S5N-MA-5-B01-PP	952021201		
			 IO-Link	S5N-MA-5-B01-OZ	952022160		
			NPN	S5N-MR-2-B01-NN	952021601		
	LED, Radial optic	2m Cable	PNP	S5N-MR-2-B01-PP	952021141		
		M12 Connector	NPN	S5N-MR-5-B01-NN	952021761		
			PNP	S5N-MR-5-B01-PP	952021341		
			LASER, Axial optic	2m Cable	NPN	S5N-ML-2-B01-NN	952021821
	M12 Connector	PNP		S5N-ML-2-B01-PP	952021401		
		NPN		S5N-ML-5-B01-NN	952021851		
		PNP		S5N-ML-5-B01-PP	952021441		
		 IO-Link		S5N-ML-5-B01-OZ	952022180		
		LASER, Radial optic		2m Cable	NPN	S5N-MH-2-B01-NN	952021951
	M12 Connector		PNP	S5N-MH-2-B01-PP	952021941		
			NPN	S5N-MH-5-B01-NN	952021971		
			PNP	S5N-MH-5-B01-PP	952021961		
Long Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-MA-2-C01-NN	952021511		
		M12 Connector	PNP	S5N-MA-2-C01-PP	952021011		
			NPN	S5N-MA-5-C01-NN	952021671		
			PNP	S5N-MA-5-C01-PP	952021211		
	 IO-Link		S5N-MA-5-C01-OZ	952022200			
	LED, Radial optic	2m Cable	NPN	S5N-MR-2-C01-NN	952021611		
		M12 Connector	PNP	S5N-MR-2-C01-PP	952021151		
			NPN	S5N-MR-5-C01-NN	952021771		
			PNP	S5N-MR-5-C01-PP	952021351		
	LASER, Axial optic	2m Cable	NPN	S5N-ML-2-C01-NN	952021831		
		M12 Connector	PNP	S5N-ML-2-C01-PP	952021411		
			NPN	S5N-ML-5-C01-NN	952021861		
			PNP	S5N-ML-5-C01-PP	952021451		
			 IO-Link	S5N-ML-5-C01-OZ	952022190		
			LASER, Radial optic	2m Cable	NPN	S5N-MH-2-C01-NN	952021991
	M12 Connector	PNP		S5N-MH-2-C01-PP	952021981		
		NPN		S5N-MH-5-C01-NN	952022011		
		PNP		S5N-MH-5-C01-PP	952022001		
Short Diffuse proximity	LED, Axial optic	2m Cable	NPN	S5N-MA-2-C10-NN	952021521		
		M12 Connector	PNP	S5N-MA-2-C10-PP	952021021		
			NPN	S5N-MA-5-C10-NN	952021681		
			PNP	S5N-MA-5-C10-PP	952021221		
	LED, Radial optic	2m Cable	NPN	S5N-MR-2-C10-NN	952021621		
		M12 Connector	PNP	S5N-MR-2-C10-PP	952021491		
Medium Diffuse proximity	LED, Axial optic	M12 Connector	NPN	S5N-MR-5-C10-NN	952021781		
			PNP	S5N-MR-5-C10-PP	952021481		
		2m Cable	NPN	S5N-MA-2-C21-NN	952022131		
		PNP	S5N-MA-2-C21-PP	952022121			
	LED, Radial optic	M12 Connector	NPN	S5N-MA-5-C21-NN	952022151		
			PNP	S5N-MA-5-C21-PP	952022141		
Fixed focus	LED, Axial optic	2m Cable	NPN	S5N-MA-2-D00-NN	952021531		
		M12 Connector	PNP	S5N-MA-2-D00-PP	952021031		
			NPN	S5N-MA-5-D00-NN	952021691		
			PNP	S5N-MA-5-D00-PP	952021231		
	LED, Radial optic	2m Cable	NPN	S5N-MR-2-D00-NN	952021631		
		M12 Connector	PNP	S5N-MR-2-D00-PP	952021161		
Fiber optic	LED, Axial optic	M12 Connector	NPN	S5N-MR-5-D00-NN	952021791		
			PNP	S5N-MR-5-D00-PP	952021361		
			NPN	S5N-MA-2-E01-NN	952021881		
			PNP	S5N-MA-2-E01-PP	952021041		
		M12 Connector	NPN	S5N-MA-5-E01-NN	952021891		
			PNP	S5N-MA-5-E01-PP	952021241		
Through beam receiver	LED, Axial optic	2m Cable	NPN	S5N-MA-2-F01-NN	952021541		
		M12 Connector	PNP	S5N-MA-2-F01-PP	952021051		
			NPN	S5N-MA-5-F01-NN	952021701		
			PNP	S5N-MA-5-F01-PP	952021251		
			LED, Radial optic	2m Cable	NPN	S5N-MR-2-F01-NN	952021641
				M12 Connector	PNP	S5N-MR-2-F01-PP	952021171
	NPN	S5N-MR-5-F01-NN			952021801		
	PNP	S5N-MR-5-F01-PP			952021371		
	LASER, Axial optic	2m Cable	NPN	S5N-ML-2-F01-NN	952021841		
		M12 Connector	PNP	S5N-ML-2-F01-PP	952021421		
			NPN	S5N-ML-5-F01-NN	952021871		
			PNP	S5N-ML-5-F01-PP	952021461		
LASER, Radial optic	2m Cable	NPN	S5N-MH-2-F01-NN	952022031			
	M12 Connector	PNP	S5N-MH-2-F01-PP	952022021			
		NPN	S5N-MH-5-F01-NN	952022051			
		PNP	S5N-MH-5-F01-PP	952022041			

S5N - METAL HOUSING - NO/NC STANDARD OUTPUT & IO-LINK MODELS (S5N-MA...PP/NN/OZ)

Through beam emitter	LED, Axial optic	2m Cable	-	S5N-MA-2-G00-XG	952021061
		M12 Connector	-	S5N-MA-5-G00-XG	952021261
	LED, Radial optic	2m Cable	-	S5N-MR-2-G00-XG	952021181
		M12 Connector	-	S5N-MR-5-G00-XG	952021381
	LASER, Axial optic	2m Cable	-	S5N-ML-2-G00-XG	952021431
		M12 Connector		S5N-ML-5-G00-XG	952021471
	LASER, Radial optic	2m Cable	-	S5N-MH-2-G00-XG	952022061
		M12 Connector	-	S5N-MH-5-G00-XG	952022071
Background suppression	LED, Axial optic	2m Cable	NPN	S5N-MA-2-M03-NN	952021551
			PNP	S5N-MA-2-M03-PP	952021071
Background suppression	LED, Axial optic	M12 Connector	PNP	S5N-MA-5-M03-PP	952021271
			 IO-Link	S5N-MA-5-M03-OZ	952022170
	LED, Radial optic		PNP	S5N-MS-5-M03-PP	952021931
Retroreflective for transparent	LED, Axial optic	2m Cable	PNP	S5N-MS-2-M03-PP	952021911
			NPN	S5N-MA-2-T01-NN	952021571
		M12 Connector	PNP	S5N-MA-2-T01-PP	952021091
			NPN	S5N-MA-5-T01-NN	952021731
	LED, Radial optic	2m Cable	PNP	S5N-MA-5-T01-PP	952021291
			NPN	S5N-MR-2-T01-NN	952021651
		M12 Connector	PNP	S5N-MR-2-T01-PP	952021191
			NPN	S5N-MR-5-T01-NN	952021811
			PNP	S5N-MR-5-T01-PP	952021391
			M12 Connector	PNP	S5N-MA-5-U03-PP
Luminescence	LED, Axial optic	2m Cable	PNP	S5N-MA-2-W03-PP	952021111
Contrast		M12 Connector	NPN	S5N-MA-5-W03-NN	952021751
			PNP	S5N-MA-5-W03-PP	952021311

S5N - METAL HOUSING - L/D INPUT MODELS MODELS (S5N-MA...PK/NK)


Retroreflective	LED, Axial optic	M12 Connector	NPN	S5N-MA-5-A00-NK	952701802	
Polarized retroreflective			PNP	S5N-MA-5-A00-PK	952701532	
			NPN	S5N-MA-5-B01-NK	952701812	
			PNP	S5N-MA-5-B01-PK	952701762	
		Diffuse proximity	2m Cable	NPN	S5N-MA-2-C01-NK	952701622
PNP				S5N-MA-2-C01-PK	952701562	
M12 Connector			NPN	S5N-MA-5-C01-NK	952701822	
			PNP	S5N-MA-5-C01-PK	952701772	
2m Cable			NPN	S5N-MA-2-C10-NK	952701632	
			PNP	S5N-MA-2-C10-PK	952701572	
Through beam receiver			M12 Connector	NPN	S5N-MA-5-C10-NK	952701832
				PNP	S5N-MA-5-C10-PK	952701522
		NPN		S5N-MA-5-F00-NK	952701842	
		PNP		S5N-MA-5-F00-PK	952701782	
Through beam emitter	LED, Axial optic	2m Cable	—	S5N-MA-2-G00-XG	952021061	
		M12 Connector	—	S5N-MA-5-G00-XG	952021261	
	LED, Radial optic	2m Cable	—	S5N-MR-2-G00-XG	952021181	
		M12 Connector	—	S5N-MR-5-G00-XG	952021381	
	LED, Axial optic	2m Cable	—	S5N-ML-2-G00-XG	952021431	
		M12 Connector		S5N-ML-5-G00-XG	952021471	
	LED, Radial optic	2m Cable	—	S5N-MH-2-G00-XG	952022061	
		M12 Connector	—	S5N-MH-5-G00-XG	952022071	

S5N - INOX HOUSING - L/D INPUT MODELS MODELS (S5N-NA...)


Polarized retroreflective	LED, Axial optic	M12 Connector	NPN	S5N-NA-5-B01-NK	952301461
Diffuse proximity Inox			PNP	S5N-NA-5-B01-PK	952301381
			NPN	S5N-NA-5-C11-NK	952301481
Through beam receiver Inox			PNP	S5N-NA-5-C11-PK	952301401
			NPN	S5N-NA-5-F01-NK	952301511
Through beam emitter inox			PNP	S5N-NA-5-F01-PK	952301431
			-	S5N-NA-5-G01-XG	952301441
Background suppression inox			NPN	S5N-NA-5-M01-NK	952301501
			PNP	S5N-NA-5-M01-PK	952301421
Retroreflective for transparent inox			NPN	S5N-NA-5-T01-NK	952301471
			PNP	S5N-NA-5-T01-PK	952301391

ACCESSORIES


ST-5010




ST-5011




ST-5012




ST-5017




SWING-18





SP-40




JOINT 18



MICRO 18



M18 FLARED PLASTIC NUT



mm

MODEL	DESCRIPTION	ORDER No.
ST-5010	M18/14 mounting bracket	95ACC5230
ST-5011	M18 mounting bracket short	95ACC5240
ST-5012	M18 mounting bracket long	95ACC5250
ST-5017	M18 mounting bracket	95ACC5270
S50 EASY -IN	M18/14 EASY in™ adjustable mounting support	95ACC 5300
JOINT -18	M18 jointed support	95ACC 5220
MICRO -18	support with micrometric regulation for tubular M18 sensors	95ACC 1380
SP-40	mounting bracket tubular	95ACC1370
SWING-18	adjustable support for M18 tubular sensors	895000006
PLASTIC NUT	flared mounting nut	95ACC2630
M18 FLARED NUT	S5N mounting nut M18 flared nut (1 pc)	95ACC2630
M18 METAL NUT	S5N mounting nut M18 nut (1 pc)	G602000017
M18 PLASTIC NUT KIT	S5N mounting nut M18 nuts kit (100 pcs)	G602000008
MEK -PROOF	front protection (only for metal models)	G5000001

IO-LINK CONNECTIVITY

MODEL	DESCRIPTION	ORDER No.
CBX-8IOL-EIP	CBX-8IOL-EIP 8P IOL M12 EIP MASTER	95ACC8180
CBX-8IOL-PNIO	CBX-8IOL-PNIO 8P IOL M12 PROFINET MASTER	95ACC8190

CABLES

TYPE	DESCRIPTION	LENGTH	MODEL	ORDER No.
Axial M12 Connector	4-pole, grey, P.V.C.	3 m	CS-A1-02-G-03	95A251380
		5 m	CS-A1-02-G-05	95A251270
		7 m	CS-A1-02-G-07	95A251280
		10 m	CS-A1-02-G-10	95A251390
	4-pole, P.U.R.	2 m	CS-A1-02-R-02	95A251540
		5 m	CS-A1-02-R-05	95A251560
Radial M12 Connector	4-pole, grey, P.V.C.	3 m	CS-A2-02-G-03	95A251360
		5 m	CS-A2-02-G-05	95A251240
		7 m	CS-A2-02-G-07	95A251245
		10 m	CS-A2-02-G-10	95A251260
	4-pole, P.U.R.	2 m	CS-A2-02-R-02	95A251550
		5 m	CS-A2-02-R-05	95A251570
Radial M12 Connector with LED (for PNP N.O. sensors)	4-pole, grey, P.V.C.	3 m	CS-A2-12-G-03	95A251400
		5 m	CS-A2-12-G-05	95A251350
		10 m	CS-A2-12-G-10	95A251370
Axial M12 Connector	4-pole, shielded, black, P.V.C.	3 m	CV-A1-22-B-03	95ACC1480
		5 m	CV-A1-22-B-05	95ACC1490
		10 m	CV-A1-22-B-10	95ACC1500
		15 m	CV-A1-22-B-15	95ACC2070
		25 m	CV-A1-22-B-25	95ACC2090
Radial M12 Connector	4-pole, shielded, black, P.V.C.	3 m	CV-A2-22-B-03	95ACC1540
		5 m	CV-A2-22-B-05	95ACC1550
		10 m	CV-A2-22-B-10	95ACC1560
Axial M12 Connector	4-pole, U.L., black, P.V.C.	3 m	CS-A1-02-U-03	95ASE1120
		5 m	CS-A1-02-U-05	95ASE1130
		10 m	CS-A1-02-U-10	95ASE1140
		15 m	CS-A1-02-U-15	95ASE1150
		25 m	CS-A1-02-U-25	95ASE1160
	4-pole, black	Connector- not cabled	CS-A1-02-B-NC	G5085002
Radial M12 Connector	4-pole, black	Connector- not cabled	CS-A2-02-B-NC	G5085003
Axial M12 Connector	5-pole, L coded power cable	3 m	CS-M1-02-B-03	95ACC0007
Axial M12 F/M12 M Connector	4-pole, double headed	3 m	CS-I1-02-B-03	95ACC0009

00,11/2021

DATALOGIC PRODUCT OFFERING



Sensors



Hand Held
scanners



Mobile Computers



Laser Marking
Systems



Safety Laser
Scanner



Vision
Systems



Stationary
Industrial
Scanners



Safety Light
Curtains